



SECOND FLOOR PLAN  
SCALE 1/4" = 1'-0"

- GREEN BUILDING NOTES:
1. TOPSOIL SHALL BE STOCKPILED ONSITE UNTIL FINAL GRADING
  2. NOT USED
  3. NOT USED

4. ALL WOOD USED FOR FRAMING SHALL BE FSC (FOREST STEWARDSHIP COUNCIL) CERTIFIED. THIS TYPE OF WOOD IS COMMONLY AVAILABLE FROM LOWES AND HOME DEPOT.
5. CONSTRUCTION MATERIALS SHALL BE RECYCLED AS FOLLOWS:
  - A. GYPSUM BOARD SCRAP WILL BE LANDFILLED ON SITE
  - B. WOOD WASTE (EXCEPT TREATED WOOD) WILL BE STORED ON SITE FOR REUSE AS FIREWOOD
  - C. RELATED WOOD WASTE WILL BE HAULED TO THE CONTRACTOR'S OFFICE FOR REUSE AS TOUCH-UP PAINT.
  - D. OTHER CONSTRUCTION WASTES WILL BE CONSIDERED FOR RECYCLING ON A CASE BY CASE BASIS.
6. ALL INSULATION SHALL BE CELLULOSE WITH FIRE RETARDANT CHEMICAL, MADE OF RECYCLED PAPER.
7. CONTRACTOR SHALL DOCUMENT ANY MATERIALS USED IN CONSTRUCTION THAT CONTAIN POST-CONSUMER RECYCLED CONTENT OR REDUCED VOC/FORMALDEHYDE CONTENT.

DATE	17MAY06
DESIGNED	LOL
DRAWN	LOL
DRAFT CHECK	LOL
DESIGN CHECK	

NO.	DESCRIPTION	BY	CHK	DATE
1	BID SET	LOL	LOL	3-17-06
	CHANGE ORDER #1	LOL	LOL	06-05-06

SECOND FLOOR PLAN  
LILE-MICHAELIEU RESIDENCE